



TARGET



Trusted Name in Indication Industry

An ISO 9001-2000 Certified



LED base



Lamp base

Revolving Light

- Housing : Acrylonitrile Butadine Styrene
 Cap : Polycarbonate
 Cap Colour : Red, Amber, Green, Clear, Blue (Clear Cap with Blue LED)
 Input Voltage : 12V, 24V DC, 110V AC, 230V AC,



Mounting Rod



Tower Light

Steady + Flashing + Revolving + Buzzer

- Housing : Acrylonitrile Butadine Styrene
 Cap : Styrene Acrylonitrile
 Cap Colours : Red, Amber, Green, Blue, Clear
 Input Voltage : 12V, 24V AC/DC, 110V AC, 220V AC
 Version : Lamp & LED



Electronic Hooter with Tower Light

- Housing : Acrylonitrile Butadine Styrene
 Mounting : Base / Wall
 Cap : Styrene Acrylonitrile
 Cap Colour : Red, Amber, Green, Blue, Clear
 Tone : Red Cabinet → Siren,
 Black Cabinet → Intermittent
 Input Voltage : 12V, 24V AC/DC, 110V, 220V AC
 Version : Lamp & LED
 Available up to 3 Stack



Electronic Hooter- 96mm x 96mm

Housing : Acrylonitrile Butadine Styrene
 Audible Range : 100db approx.
 Mounting : Flush/Base/Wall
 Tone : Red Cabinet → Siren,
 Black Cabinet → Intermittent
 Input Voltage : 9V, 12V, 24/30V, 48/50V, 110V,
 230V AC or DC

Volume control & Acceptance version available on request



Electronic Hooter- 72mm x 72mm

Housing : Acrylonitrile Butadine Styrene
 Audible Range : 90db approx.
 Mounting : Flush / Base / Wall
 Tone : Selectable 3 Tone
 Input Voltage : 12V, 24/30V, 48/50V, 110V, 230V AC or DC



Electronic Hooter- 144mm x 144mm

Housing : M. S. Powder Coated
 Audible Range : 10db approx.
 Mounting : Base
 Tone : Intermittent / Siren
 Input Voltage : 12V, 24/30V, 48/50V, 110V, 230V AC or DC



Electronic Hooter with Revolving Light

Hooter Size : 96mm x 96mm
 Housing : Acrylonitrile Butadine Styrene
 Cap : Polycarbonate
 Audible Range : 100db approx.
 Revolving : LED Version
 Mounting : Base/Wall
 Tone : Red Cabinet → Siren,
 Black Cabinet → Intermittent

Hooter Size : 144mm x 144mm
 Housing : M. S. Powder Coated
 Cap : Styrene Acrylonitrile
 Revolving : LED Version
 Mounting : Base/Wall
 Tone : Intermittent/Siren
 Audible Range : 110db Approx.
 Cap Colour : Red, Amber, Green, Blue, Clear
 Input Voltage : 12V, 24/30V, 48/50V, 110V, 230V AC or DC



Electronic Hooter with Flasher

Hooter Size : 96mm x 96mm
 Housing : Acrylonitrile Butadine Styrene
 Cap : Styrene Acrylonitrile
 Mounting : Base/Wall
 Flasher : 12V, 3 Watt. Lamp or LED
 Tone : Red Cabinet → Siren,
 Black Cabinet → Intermittent

Hooter Size : 144mm x 144mm
 Housing : M.S. Powder Coating
 Cap : Styrene Acrylonitrile
 Flasher : LED
 Mounting : Base/Wall
 Tone : Intermittent / Siren

Cap Colour : Red, Amber, Green, Blue
 Input Voltage : 12V, 24/30V, 48/50V, 110V, 230V AC or 115V AC



Flasher with LED

Housing : Acrylonitrile Butadine Styrene
 Cap : Styrene Acrylonitrile
 Cap Colour : Red, Amber, Green, Blue,
 Input Voltage : 12V, 24V DC, 110V, 230V AC



Busbar Indication

Housing : M.S. Powder Coated
 Cap : Polystyrene
 Cap Colour : Red, Amber, Blue
 Input Voltage : 230V AC



Aviation Light /Obstruction Light Dome

Housing : Pressure Cast
 Cap : Polycarbonate

- * LED based obstruction lights utilize 90% less power than an equivalent incandescent
- * Typical power consumption-@230VAC-15W.
- * Weather/Corrosion resistant lamp assembly and housing.
- * Self contained wiring compartment eliminate additional boxes
- * Can be used as steady or flashing lights.
- * Nos. of LEDs used-306 nos.
- * Available in 12-24V DC, 110V AC and 230V AC (50/60/HZ) version
- * Automatic on & off using Photo switch version available.



Compact

Housing : Base & Top Powder coated Aluminum Casting
 Cap : Polycarbonate
 Input : 85V to 250V ACDC,
 24V to 80V ACDC, 12V DC
 Version : LED with Photo Sensor

Compact



Base Mounting

Housing : Cast Aluminium
 Cover : Plastic
 Size : 4" (Base Mounting
 95mm approx.)
 Input Voltage : 24V, 110V, 230V AC



Flush Mounting

Housing : Cast Aluminum,
 Cover : Plastic
 Size : Top-100mm Ø approx.
 Base-72mm Ø approx.
 Input Voltage : 24V, 110V, 230V AC



Base Mounting

Housing : Cast Aluminium
 Size : 6" (Base Mounting
 173mm approx.)
 Input Voltage : 24V, 110V, 230V AC

Electrical Hooter



Industrial Gong Bell

Housing : Cast Aluminium
 Gong Size : 3"(75mm),
 4"(100mm),
 6"(150mm),
 8"(200mm),
 9"(250mm) &
 12"(300mm)
 Gong : Mild pressed,
 Heavy chrome plated
 (Mirror finish Gong)
 Input Voltage : 9V, 12V, 24/30V,
 48/50V, 110V, 230V
 AC or DC



Motorised Siren

Housing : Cast Aluminium
 Type : Vertical or Horizontal
 Single or Double
 Mounting
 Range : 0.10 kms .
 up to 16.00 kms.
 Input Voltage : 12V, 24V, 48V,
 110V, 220V AC or DC
 or 415V AC
 Version : Electrically, Battery &
 Hand operated



Electrical Square Buzzer

Housing : Cast Aluminium
 Cover : Plastic
 Size : Flush Mounting
 52mm x 52mm approx.
 Input Voltage : 24V, 110V, 230V AC

Manufactured by :

TARGET ELECTRICALS

7A, Tawawalla Building,
 147, Lohar Chawl,
 Mumbai 400002.

Tel.: 91-22-2200 5703

Fax : 91- 22- 2205 6937

Email: targetel@bom5.vsnl.net.in

Website: targetel.com



• All rights reserve to change in design, model & material dimension are with manufacturer. Colours shown in the picture may not match with the actual colours.